



Iron Woods Decking Take Off Form

Please review Iron Woods Best Practices Guide before completing form.

1) Coverage

SQ FT _____

2) Wood Type

Iron Woods Premium Select Ipe _____

Iron Woods Premium Select Garapa Gold _____

Iron Woods Premium Select Dark Red Balau _____

*Iron Woods decking is only available Kiln Dried and Pre- equalized to 12-14% moisture content.

3) Fastener Type

Face Screw _____ Screw and Plug _____ Hidden Fastener _____

4) Deck Dimension – Select One

1x4 (net .75"x3.5") Grooved (Well Ventilated Deck Only) _____

1x4 (net .75"x3.5") Non-Grooved (Well Ventilated Deck Only) _____

1x4 (net 11/16"x3" face) T&G Porch Floor (Covered Porch Only) _____

1x6 (net .75"x5.5") Grooved (Not Recommended)

1x6 (net .75"x5.5") Non-Grooved (Well Ventilated Deck Only) _____

5/4x4 (net 1"x3.5") Grooved (Well or Poorly Ventilated Deck) _____

5/4x4 (net 1"x3.5") Non-Grooved (Well or Poorly Ventilated Deck) _____

5/4x6 (net 1"x5.5") Grooved (Well Ventilated Deck Only) _____

5/4x6 (net 1"x5.5") Non-Grooved (Well Ventilated Deck Only) _____

*Any Deck which is less than 12" below stringers in elevation and or fully wrapped preventing airflow, regardless of elevation, will be considered a Poorly Ventilated Deck.

5) Skirting Requirement

6" (net 5.5") _____ 8" (net 7.25") _____ 10" (net 9.25") _____ 12" (net 11.25") _____

Lineal Ft Required _____

6) Stringer Spacing– Select One

16" _____ 24" _____

*New Construction Recommend Double Stringers 24" On Center

7) Deck will be finished _____ Left to weather naturally _____